

Less than 45 in of table space required

# **iLux Pro Dental 3D Printing Solution**

LuxCreo's iLux Pro Dental is a desktop DLP 3D printer that offers high performance functionality with industrial-grade resolution and printing speed, which is ideal for rapid printing of dental industry.

Equipped with LEAP™ platform, LuxCreo has developed resin materials for orthodontic appliances such as dental models, splints / night guards, and retainers and clear aligners of high resolution, superb transparency, yet low cost. iLux Pro Dental is also compatible with third party resins to meet various printing requirements of dental industry.

iLux Pro Dental is connected to LuxCreo's software ecosystem to realize smart operations such as lightweight design, high-speed slicing, device interconnection, and smart factory management.

# World First FDA Class II 510 (k) Direct Print Clear Aligner





# A Complete, Tailored, Integrated, Workflow



Optimized materials Simple, automated software

## SYSTEM SPECIFICATIONS

Build Volume (XYZ) 192 × 108 x 200 mm (7.6 x 4.3 x 7.9 in)

Pixel Pitch (XY)  $50 \, \mu m$  Wavelength  $385 \, nm$ 

3D Printer Uncrated(WxDxH) 457 x 551 x 551 mm (18 x 21.7 x 21.7 in)
3D Printer Door Open(WxDxH) 457 x 583 x 698 mm (18 x 23 x 27.5 in)

3D Printer Uncrated Weight 35.5 kg (78.3 lbs)
Certifications FCC, CE, UL

Warranty 12 months manufacturer's warranty included

Extended warranty options available

### • MATERIALS

 ${\sf Compatible\ Materials} \qquad \qquad {\sf PromptSmile^{TM}\ Denture\ Base,\ PromptSmile^{TM}\ Denture\ Teeth}$ 

DNG Soft, DNG Hard, DMR, DSG, DCA KeySplint Soft, Keystone IBT

Dreve FotoDent Guide, Dreve FotoDent Gingiva, Dreve FotoDent Tray2

### • SOFTWARE AND NETWORK

Software LuxFlow, LuxDesign
Connectivity USB/Ethernet/WiFi

# **Digital Polishing™**

Digital Polishing $^{\text{TM}}$  is a revolutionary LuxCreo solution, enabling incredibly clear appliances direct from the printer without the manual polishing required from competing solutions.



Revenue with same workforce



80% Higher clarity



**75%**Reduction in polishing time



# **LuxCreo Resins**



# **Available 3rd Party Resins**













# iLuxWash Dental



iLuxWash Dental enhances the ultrasonic cleaning process by adding a magnetic-driven impeller stirring function. This rapidly agitates the cleaning solution during ultrasonic cleaning while also featuring a heating function, making it more effective in removing residual resin from printed parts.

Driven by a focus on improving user experience, the fully-automatic intelligent operating system enables unattended and automatic operations. This helps prevent distortion issues that may arise from over-soaking printed parts, making iLuxWash Dental the best choice in the dental and medical fields.

#### SYSTEM SPECIFICATIONS

 Washing Volume(XYZ)
 158 x 158 x 148 mm(6.2 x 6.2 x 5.8 in)

 Exterior Dimension Uncrated
 200 x 488 x 418 mm(7.9 x 19.2 x 16.5 in)

 Exterior Dimension Crated
 335 x 615 x 525 mm(13.2 x 24.2 x 20.7 in)

Uncrated Weight 21 kg(46.3 lbs)

Crated Weight 25.5 kg(56.2 lbs)

Heating Temperature  $\leq$  60°C (140 °F)

### SUGGESTED OPERATING ENVIRONMENT

Temperature 22-32 °C (72-90 °F)

Humidity (RH) < 80%

Power Requirement 100-120 VAC, 50/60 Hz, 600 W

200-240 VAC, 50/60 Hz, 600 W



### **LuxFresh Detergent**

LuxFresh is a non-IPA wash detergent for the iLuxWash Dental. LuxFresh can be heated for superior cleaning, compared to IPA, and is more office-friendly with higher reusability, low odor, and is non-flammable. The one-touch operation is completed in less than 15 minutes when used with iLuxWash Dental.





iLuxCure Pro offers best user experience and convenience by providing unique upward and downward high intensity lighting, heating function, and 360° curing coverage. It is ideal for dental and medical, industrial, and R&D applications.

### SYSTEM SPECIFICATIONS

Curing Volume (XYZ) Φ200 x 200 mm (Φ7.9 x 7.9 in)

Exterior Dimensions Uncrated  $320 \times 361 \times 460 \text{ mm}$  (12.6 x 14.2 x 18.1 in)

 Uncrated Weight
 21.5 kg (47.4 lbs)

 Wavelength
 405 + 385 nm

 Uniformity
 ≥ 95% w/ turntable

 Heating Temperature
 ≤ 60°C (140 °F)

### SUGGESTED OPERATING ENVIRONMENT

Temperature 22-32 °C (72-90 °F)

Humidity (RH) < 80%

Input Voltage AC 100~120V, 50/60Hz, 9A

AC 200~240V, 50/60Hz, 4.5A





**LuxDesign** enables automatic aligner/retainer shell generation; LuxDesign helps orthodontists and dentists easily transfer from dental model design to clear aligner/retainer design. Together with the printing software, LuxFlow, which has functions specially developed for dental, allows users to finish the design smoothly and send to dental desktop printers for direct printing.

## Ask us about our treatment capabilities.













LuxFlow is an automated software featuring highly customized functions including model processing, support generation, and slicing for different dental models.



Compared with other pre-processing software, LuxFlow is featured with its customized functions for targeted industries such as dental, footwear, eyewear, and elastic printing. Based on the technical knowhow from mass production of different applications, LuxFlow serves as the best tool to prepare your 3D model in less time, with less material, and at a higher printing success rate.





# **Direct Print Aligner and Retainer Workflow**













Post-processing

**Buffing and Washing** 

**Total Active Labor Per Aligner** 

1.5 min

# Traditional Thermoformed Workflow








Mold

Generation



Printing



Post-

processing



Manual





Manual

Trimming



Thermal

Buffing and Washing

Total Active Labor Per Aligner

5.5 min

3-10x Grow your business \* with same workforce!

### North America Headquarter

+1 (650) 336-0888 / info@luxcreo.com www.LuxCreo.com 940 Old County Rd., Belmont, CA 94002, U.S.A.

